



Model/Number	6010 (Blue)	6020 (Amber)	6030 (Red)	6090 (CoolWhite)
Size in Inches(Strip only): Strip With one(1) End to End	11 11/16" Long	11 11/16" Long	11 11/16" Long	11 11/16" Long
Connector:	11 7/8" Long	11 7/8" Long	11 7/8" Long	11 7/8" Long
Width in Inches:	0.10"	0.10"	0.10"	0.10"
Height in Inches:	0.40"	0.40"	0.40"	0.40"
Power Requirement:	12v DC, 75mA max	12v DC, 75mA max	12v DC, 75mA max	12v DC, 75mA max
Power Consumption:	0.72watts per/pc.	0.72watts per/pc.	0.72watts per/pc.	0.72watts per/pc.
Mounting Method:	3M Double Sided Tape	3M Double Sided Tape	3M Double Sided Tape	3M Double Sided Tape
One(1) Single LED Intensity (1 of 12 per Strip):	70 mcd	80 mcd	80 mcd	230 mcd
Unite of Measure:	mcd=millicandela	mcd=millicandela	mcd=millicandela	mcd=millicandela
LED View Angle:	120° ± 10°	120° ± 10°	120° ± 10°	120° ± 10°
Water Resistance IP64:	Ingress Protection, Dust Tight, Protected against splashing water	Ingress Protection, Dust Tight, Protected against splashing water	Ingress Protection, Dust Tight, Protected against splashing water	Ingress Protection, Dust Tight, Protected against splashing water
Flat Strip for easy installation:	Scissor marks indicate cutting locations when cutting is necessary	Scissor marks indicate cutting locations when cutting is necessary	Scissor marks indicate cutting locations when cutting is necessary	Scissor marks indicate cutting locations when cutting is necessary
Packaging For All Colors	Number per Box/Size/Weight: 20/1.45 x 1.45 x 12.5/8.0 oz			

All other brands or product names are trademarks or registered trademarks of their respective owners. Specifications are subject to change without notice. iSky strives to use only materials that carry ASTM E84 Class A or 1 fire rating. Low voltage lighting-- not all materials carry an independent lab listing. iSky uses patent pending technology and design.